AT 603 - Technical Specifications

Description	AT 603 is a bias agro-industrial tire for implement machinery and backhoe loaders. AT 603 has been engineered to ensure great durability and traction on drive wheels providing best performance on every surface as well as excellent self-cleaning properties. The AT 603 "special" version has a reinforced casing, while the "HD" version offers improved cut and chip resistance.
UM	International Standard
Construction	BIAS
Machinery	Agriculture: Backhoe Loader, Implement Machinery Industrial: Backhoe Loader

Version	*STANDARD*
Type	*TL*
Tyre Size	*15.5 - 25*

Dimensions International Standard

Ply Rating	*12*
Section Width (mm)	*410*
Overall Diameter (mm)	*1265*
Static Loaded Radius (mm)	*577*
Rolling Circumference (mm)	*3861*
Rim Rec	*12.00/1.3*
Rim Alt	*12.00/1.3 (DC)*
TRA Code	*E2/G2/L2*

Load capacity (Kg)

km/h / bar	2.50	4.00	2.50
50	3250	-	-
10	-	5600	-
40	-	-	2650

Printed on 06/01/2021 05:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..