EARTHMAX SR 23 - Technical Specifications

Description	EARTHMAX SR 23 (G-2/L-2) is an All Steel radial tire specially designed for motor graders and loaders. It features superior forward and lateral traction as well as exceptional self-cleaning properties. The durable casing and the particularly cut-resistant tread provide a long service life.
UM	International Standard
Construction	RADIAL
Machinery	OTR: Grader, Loader

Version	*CUT RESISTANT COMPOUND*
Type	*TL*
Tyre Size	*20.5 R 25*
LI/SS	*161 A8/186 A2*

Dimensions International Standard

Overall Width (mm)	*535*
Overall Diameter (mm)	*1490*
Static Loaded Radius (mm)	*668*
Rolling Circumference (mm)	*4489*
Rim Rec	*17.00/2.0*
Star Rating	*
TRA Code	*G2/L2*

Load capacity (Kg)

km/h / bar	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	4.00	4.25	4.50	4.75	5.00
40	2430	2800	3150	3450	3875	4125	4375	4625	---	--	--	--	--
10	--	--	--	--	--	--	--	--	8000	8250	8750	9000	9500

Printed on 06/01/2021 07:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of

its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..