EARTHMAX SR 30 - Technical Specifications

Description	EARTHMAX SR 30 (E-3/L-3) is an *All Steel* radial tire which is dual-purposed for loaders and articulated dump trucks. The multi-layer steel belts and the rigid block pattern provide excellent traction, stability and durability. The special cut-resistant compound makes EARTHMAX SR 30 the ideal solution for a variety of harsh operating conditions.
UM	International Standard
Construction	RADIAL
Machinery	OTR: Articulated Dump Truck (ADT), Dozer, Loader

Version	*CUT RESISTANT COMPOUND*
Type	*TL*
Tyre Size	*17.5 R 25*
LI/SS	*167 B/176 A2*

Dimensions International Standard

TKPH	*150*
Overall Width (mm)	*446*
Overall Diameter (mm)	*1347*
Static Loaded Radius (mm)	*606*
Rolling Circumference (mm)	*4021*
Rim Rec	*14.00/1.5*
Rim Alt	*14.00/1.3 (DC), 13.00/1.4 (DC)*
Star Rating	***/**
TRA Code	*E3/L3*

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	4375	4625	4750	5000	5150	5450
10	6000	6150	6500	6700	7100	-

Printed on 06/01/2021 06:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..