EARTHMAX SR 41 - Technical Specifications

Description	EARTHMAX SR 41 is an All Steel radial tire perfect for Articulated Dump Trucks, Loaders and Dozers. Thanks to its all steel structure and special block pattern, EARTHMAX SR 41 provides excellent resistance against punctures and an extended service life. In addition to long working hours without downtime, the tire ensures extraordinary comfort.
UM	International Standard
Construction	RADIAL
Machinery	OTR: Articulated Dump Truck (ADT), Dozer, Loader

Version	*CUT RESISTANT COMPOUND*
Type	*TL*
Tyre Size	*29.5 R 25*
LI/SS	*200 B*

Dimensions International Standard

TKPH	*225*
Overall Width (mm)	*761*
Overall Diameter (mm)	*1861*
Static Loaded Radius (mm)	*830*
Rolling Circumference (mm)	*5510*
Rim Rec	*25.00/3.5*
Rim Alt	*25.00/3.5 IF*
Star Rating	**
TRA Code	*E4*

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	11500	11800	12500	12850	13600	14000

Printed on 06/01/2021 05:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..