EARTHMAX SR 45 - Technical Specifications

Description	EARTHMAX SR 45 is an *All Steel* radial tire specially designed for rigid haul trucks. EARTHMAX SR 45 is the ideal tire for all operations requiring high traction.
UM	International Standard
Construction	RADIAL
Machinery	OTR: Rigid Dump Truck

Version	*CUT RESISTANT COMPOUND*
Type	*TL*
Tyre Size	*18.00 R 33*
LI/SS	*191 B*

Dimensions International Standard

TKPH	*185*
Overall Width (mm)	*505*
Overall Diameter (mm)	*1870*
Static Loaded Radius (mm)	*856*
Rolling Circumference (mm)	*5608*
Rim Rec	*13.00/2.5*
Rim Alt	*--*
Star Rating	**
TRA Code	*E4*

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	8500	8750	9000	9250	9750	10000	10300	10600	10900

Printed on 06/01/2021 07:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this

publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..