MP 567 - Technical Specifications

Description	MP 567 is an agro-industrial tire suitable for field and road transport and municipality/maintenance operations. It is the perfect tire for telehandlers and implement machinery. The MP 567 tire provides good traction in all the weather conditions as well as excellent self-cleaning properties. This tire ensures a comfortable driving experience, together with a longer service life.
UM	International Standard
Construction	BIAS
Machinery	Agriculture: Implement Machinery, Telehandler Industrial: Telehandler, Universal Vehicle

Version	*STANDARD*
Type	*TL*
Tyre Size	*16.0/70 - 20* *(405/70 - 20)*

Dimensions International Standard

Ply Rating	*14*
Section Width (mm)	*405*
Overall Diameter (mm)	*1128*
Static Loaded Radius (mm)	*490*
Rolling Circumference (mm)	*3350*
Rim Rec	*13 SDC*
Rim Alt	*12*
ECE	*E4-54R-0022639*

Load capacity (Kg)

km/h / bar	3.50
90	2900
40	3340

Printed on 29/12/2020 20:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..