PAC MASTER - Technical Specifications

Description	PAC MASTER is a bias tire for compactors. It shows high stability and ensures an extended tire life-cycle. It is made of a special compound that provides particular heat resistance.
UM	International Standard
Construction	BIAS
Machinery	Industrial: Compactor

Version	*STANDARD*
Type	*TT*
Tyre Size	*11.00 - 20*

Dimensions International Standard

Ply Rating	*18*
Section Width (mm)	*291*
Overall Diameter (mm)	*1070*
Static Loaded Radius (mm)	*494*
Rolling Circumference (mm)	*3310*
Rim Rec	*8.0*
Rim Alt	*8.5*
ECE	*E11-106R-006177*

Load capacity (Kg)

km/h / bar	8.25
10	5800
15	4625

Printed on 06/01/2021 07:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not

permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..