PL 801 - Technical Specifications

Description	PL 801 has been specially designed for hay harvesting applications with rotor rakes/tedders and for logistics operations with forklifts. It features excellent stability as well as high cut and chip resistance. PL 801 ensures an extended tire life-cycle.
UM	International Standard
Construction	BIAS
Machinery	Agriculture: Hay Harvester, Rotor Rake / Tedder, Forklift Industrial: Forklift

Version	*STANDARD*
Type	*TT*
Tyre Size	*7.00 - 12*

Dimensions International Standard

Ply Rating	*12*
Section Width (mm)	*189*
Overall Diameter (mm)	*692*
Rim Rec	*5.00 S*
ECE	*E11-106R-003567*

Load capacity (Kg)

km/h / bar	8.50
25 LOAD WHEEL	2680
25 STEER WHEEL	2060
10 OTHER VEHICLES	2680
25 OTHER VEHICLES	2060
STATIC SIDE LOADER	3110

Printed on 05/01/2021 13:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this

publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..