SKID POWER - Technical Specifications

Description	SKID POWER has been designed for skid steers in construction applications. It shows excellent traction as well as enhanced self-cleaning features. The tire features an extra deep tread along with extra sidewall protection providing excellent cut and chip resistance and outstanding durability. SKID POWER is the ideal tire for loose surfaces.
UM	International Standard
Construction	BIAS
Machinery	Industrial: Skid Steer

Version	*STANDARD*
Type	*TL*
Tyre Size	*10 - 16.5*

Dimensions International Standard

Ply Rating	*10*
Section Width (mm)	*254*
Overall Diameter (mm)	*775*
Static Loaded Radius (mm)	*355*
Rolling Circumference (mm)	*2286*
Rim Rec	*8.25*

Load capacity (Kg)

km/h / bar	5.20
10	2135
15	1685
25	1560

Printed on 06/01/2021 05:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this

publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..