XL GRIP IND3 (RTG) - Technical Specifications

Description	XL GRIP (IND-3) is a bias-ply tire for RTG cranes in stacking and lifting applications. The tire features a strong casing made of a specially formulated tread compound, which provides an extended tire life-cycle.
UM	International Standard
Construction	BIAS
Machinery	Industrial: RTG Crane

Version	*INDUSTRIAL*
Type	*TL*
Tyre Size	*16.00 - 25*

Dimensions International Standard

Ply Rating	*32*
Overall Width (mm)	*465*
Overall Diameter (mm)	*1485*
Static Loaded Radius (mm)	*682*
Rolling Circumference (mm)	*4395*
Rim Rec	*11.25/2.0*
Rim Alt	*13.00/2.0*
TRA Code	*IND3*

Load capacity (Kg)

km/h / bar	10.00
10	16875

Printed on 06/01/2021 07:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not

permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..