EARTHMAX SR 23 - Technical Specifications

Description	EARTHMAX SR 23 (G-2/L-2) is an All Steel radial tire specially designed for motor graders and loaders. It features superior forward and lateral traction as well as exceptional self-cleaning properties. The durable casing and the particularly cut-resistant tread provide a long service life.
UM	International Standard
Construction	RADIAL
Machinery	OTR: Grader, Loader

Version	*CUT RESISTANT COMPOUND*
Type	*TL*
Tyre Size	*15.5 R 25*
LI/SS	*146 A8/169 A2*

Dimensions International Standard

Overall Width (mm)	*383*
Overall Diameter (mm)	*1264*
Static Loaded Radius (mm)	*559*
Rolling Circumference (mm)	*3756*
Rim Rec	*12.00/1.3*
Star Rating	*
TRA Code	*G2/L2*

Load capacity (Kg)

km/h / bar	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	4.00	4.25	4.50	4.75	5.00
40	1550	1750	2000	2180	2360	2575	2800	3000	-	-	-	-	-
10	-	-	-	-	-	-	-	-	5000	5150	5450	5600	5800

Printed on 22/06/2021 07:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of

its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..