EARTHMAX SR 32 - Technical Specifications

Description	EARTHMAX SR 32 is a non-directional wide-base radial tire particularly suitable for scrapers. The tire features a strong All Steel casing and a special tread compound providing excellent cut and puncture resistance as well as durability. Additional traits are exceptional traction and flotation even during heavy-duty operations.
UM	International Standard
Construction	RADIAL
Machinery	OTR: Scraper

Version	*CUT RESISTANT COMPOUND*
Type	*TL*
Tyre Size	*29.5 R 29*
LI/SS	*202 B*

Dimensions International Standard

TKPH	*288*
Overall Width (mm)	*765*
Overall Diameter (mm)	*1980*
Static Loaded Radius (mm)	*883*
Rolling Circumference (mm)	*6009*
Rim Rec	*25.00/3.5*
Rim Alt	*24.00/3.5*
Star Rating	**
TRA Code	*E3*

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	12150	12500	13200	13600	14500	15000

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..