EARTHMAX SR 475 - Technical Specifications

Description	EARTHMAX SR 475 is an all steel radial tire specially designed for Rigid Dump Trucks. It is ideal for hard and rocky operations especially with long hauls. The unique tread design generate lower heat in hot climate and provides excellent traction. Its strong all steel casing and belts provide great stability and resistant to snags and punctures. EARTHMAX SR 475 has been developed with squared shoulder that ensures excellent maneuverability and handling, maximizing the ground contact.
UM	International Standard
Construction	RADIAL
Machinery	OTR: Rigid Dump Truck

Version	*CUT RESISTANT COMPOUND*
Type	*TL*
Tyre Size	*18.00 R 33*
LI/SS	*191 B*

Dimensions International Standard

TKPH	*265*
Overall Width (mm)	*490*
Overall Diameter (mm)	*1860*
Static Loaded Radius (mm)	*860*
Rolling Circumference (mm)	*5721*
Rim Rec	*13.00/2.5*
Star Rating	**
TRA Code	*E4*

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	8500	8750	9000	9250	9750	10000	10300	10600	10900

Printed on 22/06/2021 07:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..