EARTHMAX SR 47 - Technical Specifications

Description	EARTHMAX SR 47 (E-4) is an *All Steel* radial tire specially designed for rigid haul trucks operating in conditions requiring maximum rock cut and puncture resistance. The E-4 tread depth and the unique tread design ensure long wear even on long hauls, thus reducing downtime and increasing productivity. Available in standard and cut-resistant compounds.
UM	International Standard
Construction	RADIAL
Machinery	OTR: Rigid Dump Truck

Version	*CUT RESISTANT COMPOUND*
Type	*TL*
Tyre Size	*18.00 R 33*
LI/SS	*195 B*

Dimensions International Standard

TKPH	*168*
Overall Width (mm)	*510*
Overall Diameter (mm)	*1885*
Static Loaded Radius (mm)	*867*
Rolling Circumference (mm)	*5674*
Rim Rec	*13.00/2.5*
Star Rating	***
TRA Code	*E4*

Load capacity (Kg)

km/h / bar	7.25	7.50	7.75	8.00
50	11200	11500	11800	12150

Printed on 22/06/2021 07:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..