EM 939 - Technical Specifications

Description	EM 939 has been specially designed for excavators in road construction applications. It has a deeper tread and more lugs ensuring an extended tire life-cycle. The special lug design provides excellent traction during on/off road operations. The tire shows best lateral traction as well as outstanding self-cleaning features. The unique tread compound offers cut and chip resistance whereas the strong casing provides a long service life.
UM	International Standard
Construction	BIAS
Machinery	Industrial: Excavator

Version	*STANDARD*
Type	*TT*
Tyre Size	*10.00-20*

Dimensions International Standard

Ply Rating	*18*
Section Width (mm)	*280*
Overall Diameter (mm)	*1075*
Rim Rec	*7.5*
Rim Alt	*7.0 ; 8.0*

Load capacity (Kg)

km/h / bar	8.50
50	3250

Printed on 22/06/2021 05:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..