TR 459 - Technical Specifications

Description	TR 459 has been particularly designed for digging and loading operations as well as municipality and maintenance applications with tractors and backhoe loaders. It offers high stability and is available in two versions. The “special” version provides an extended tire life-cycle.
UM	International Standard
Construction	BIAS
Machinery	Agriculture: Backhoe Loader, Tractor Industrial: Backhoe Loader

Version	*INDUSTRIAL*
Type	*TL*
Tyre Size	*14.9 - 24*
LI/SS	*137 A8*

Dimensions International Standard

Ply Rating	*8*
Section Width (mm)	*390*
Overall Diameter (mm)	*1244*
Static Loaded Radius (mm)	*562*
Rolling Circumference (mm)	*3657*
Rim Rec	*DW 13*
Rim Alt	*DW 12 ; DW 11 ; DW 13 L*
ECE	*E11-106R-005281*
TRA Code	*R4*

Load capacity (Kg)

km/h / bar	2.10
40	2300

Printed on 18/06/2021 07:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..