IS standard

GROWING TOGETHER

AGRIMAX
RADIAL TRACTOR TIRES

RT 945

PRODUCT DATA SHEET

Radial

R-1W

D

160

Technologies

Strong Casing

Performance

High Load Capacity

Durability

Stability

Self-Cleaning

Traction

AGRIMAX RT 945

RADIAL TRACTOR TIRES

AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. Its strong carcass gives the tire excellent stability, outstanding traction, and exceptional durability.

	Tire size	LI/SS	RIM Rec.	RIM Alt.	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
∅ 30"	420/90 R 30	147 A8/B	DW 13	W 14 L	418	1518	684	4571	700	STD
∅ 42"	320/90 R 42 (12.4 R 42)	139 A8/B	W 10	W 9 ; W 11	319	1643	760	4944	775	STD
∅ 46"	320/90 R 46 (12.4 R 46)	146 A8/B	W 10	W 9 ; W 11	319	1744	810	5232	825	STD
	320/90 R 46 (12.4 R 46)	148 D/151 A8	W 10	W 9 ; W 11	319	1744	810	5232	825	STD
	380/90 R 46 (14.9 R 46)	155 A8/B	W 12	W 11 ; W 13	380	1852	866	5648	875	STD
	380/90 R 46 (14.9 R 46)	159 A8/B	W 12	W 11 ; W 13	380	1852	859	5699	875	STD
∅ 50"	320/90 R 50 (12.4 R 50)	150 A8/B	W 10	W 9 ; W 11	319	1846	873	5618	875	STD
	380/90 R 50 (14.9 R 50)	151 A8/B	W 12	W 11 ; W 13	380	1954	906	5900	925	STD
	380/90 R 50 (14.9 R 50)	160 A8/B	W 12	W 11 ; W 13	390	1954	921	5958	925	STD
∅ 54"	320/90 R 54 (12.4 R 54)	156 A8/B	W 10	W 9 ; W 11	319	1948	930	6021	925	STD
	380/90 R 54 (14.9 R 54)	158 A8/B	W 12	W 11 ; W 13	380	2056	962	6232	975	STD

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.

EN / 02-2025

BKT GROWING TOGETHER