IS standard

BKT
GROWING TOGETHER

AGRIMAX
RADIAL TRACTOR TIRES
RT 955

PRODUCT DATA SHEET

Radial

R-1

D

154

Technologies

Strong Casing

Performance

High Load Capacity

Durability

Stability

Self-Cleaning

Traction

AGRIMAX RT 955

RADIAL TRACTOR TIRES

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
∅ 24"	210/90 R 24 (8.3 R 24)	107 A8/B	W 7	W 6	214	1010	462	3027	475	STD
∅ 28"	210/95 R 28 (8.3 R 28)	116 A8/B	W 7	W 6	214	1111	513	3364	525	STD
∅ 32"	210/95 R 32 (8.3 R 32)	120 A8/B	W 7	W 6	214	1213	571	3703	575	STD
	230/95 R 32 (9.5 R 32)	128 A8/B	W 7	W 8	228	1251	585	3810	600	STD
	270/95 R 32 (11.2 R 32)	136 A8/B	W 9	W 8 ; W 10	275	1327	614	4076	625	STD
∅ 36"	230/95 R 36 (9.5 R 36)	130 A8/B	W 7	W 8	228	1352	639	4112	650	STD
	270/80 R 36	134 A8/B	W 9	W 8 ; W 10	275	1346	629	4090	650	STD
	270/95 R 36 (11.2 R 36)	139 A8/B	W 9	W 8 ; W 10	275	1428	665	4335	675	STD
∅ 38"	270/95 R 38 (11.2 R 38)	140 A8/B	W 9	W 8 ; W 10	275	1479	697	4510	700	STD
∅ 40"	230/95 R 40 (9.5 R 40)	132 A8/B	W 7	W 8	228	1454	690	4445	700	STD
∅ 42"	230/95 R 42 (9.5 R 42)	133 A8/B	W 7	W 8	228	1506	714	4595	725	STD
	300/85 R 42 (11.2 R 42)	144 A8/B	W 9	W 10 ; W 11	295	1577	745	4850	750	STD
∅ 44"	210/95 R 44 (8.3 R 44)	120 A8/B	W 7	W 6	214	1518	721	4653	725	STD

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index

Radial

R-1

D

154

Technologies

Strong Casing

Performance

High Load Capacity

Durability

Stability

Self-Cleaning

Traction

	Tire size	LI/SS	RIM Rec.	RIM Alt.	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
∅ 44"	230/95 R 44 (9.5 R 44)	134 A8/B	W 7	W 8	228	1556	739	4788	750	STD
	270/95 R 44 (11.2 R 44)	142 A8/B	W 9	W 8 ; W 10	275	1632	764	4983	775	STD
∅ 46"	270/95 R 46 (11.2 R 46)	143 A8/B	W 9	W 8 ; W 10	275	1683	792	5169	800	STD
	300/95 R 46 (12.4 R 46)	148 A8/B	W 9	W 10 ; W 11 ; DW 10 ; DW 11	295	1738	812	5318	825	STD
	300/95 R 46 (12.4 R 46)	148 D/ 151 A8	W 9	W 10 ; W 11 ; DW 10 ; DW 11	295	1738	812	5318	825	STD
	340/85 R 46 (13.6 R 46)	150 A8/B	W 12	W 11	353	1746	826	5346	850	STD
∅ 48"	230/95 R 48 (9.5 R 48)	136 A8/B	W 7	W 8	228	1656	792	5085	800	STD
	230/95 R 48 (9.5 R 48)	136 D/ 139 A8	W 7	W 8	228	1656	792	5085	800	STD
	270/95 R 48 (11.2 R 48)	144 A8/B	W 9	W 8 ; W 10	275	1733	820	5351	825	STD
	340/85 R 48 (13.6 R 48)	152 A8/B	W 12	W 11	353	1797	855	5572	875	STD
	340/85 R 48 (13.6 R 48)	151 D/ 154 A8	W 12	W 11	353	1797	855	5572	875	STD
∅ 52"	300/95 R 52 (12.4 R 52)	151 A8/B	W 9	W 10 ; W 11 ; DW 10 ; DW 11	295	1891	889	5774	900	STD
∅ 54"	270/95 R 54 (11.2 R 54)	146 A8/B	W 9	W 8 ; W 10	275	1885	894	5815	900	STD

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.

EN / 07-2025