IS standard

GROWING TOGETHER

CON STAR

PRODUCT DATA SHEET

NEWSIZE

EN / 03-2025

Bias

A8

168

CON STAR

CON STAR is particularly suitable for compact loaders and telehandlers in agro-industrial, lifting and loading applications. It features great traction along with excellent vertical and horizontal stability. CON STAR has been made of a cut-and-chip-resistant compound contributing to an extended tire life-cycle.

Technologies

Special Compound

Performance

Stability

Traction

Cut and Chip Resistance

	Tire size	RIM Rec.	RIM Alt.	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
∅ 18"	340/80 - 18 (12.5/80 - 18)	11	12 ; 11 SDC ; 12 SDC ; W 10 ; W 11	350	1015	465	3040	IND	-	TL	143 A8
∅ 20"	340/80 - 20 (12.5/80 - 20)	11	12 ; 11 SDC ; 12 SDC ; W 10 ; W 11	350	1065	491	3272	IND	-	TL	144 A8
	380/75 - 20 (14.5 - 20)	W 12	W 11 ; 12 SDC ; 12 ; W 13 ; 13 SDC ; 13	385	1080	500	3273	IND	-	TL	148 A8
	400/70 - 20 (16.0/70 - 20)	13	12 SDC ; 13 SDC ; 14	405	1080	501	3303	IND	16	TL	149 A8
	400/70 - 20 (16.0/70 - 20)	13	12 SDC ; 13 SDC ; 14	405	1080	501	3303	IND	-	TL	156 A8
	400/70 - 20 (16.0/70 - 20) NEWSIZE	13	12 SDC ; 13 SDC ; 14	405	1080	496	3106	IND	-	TL	161 A8
∅ 24"	400/70 - 24 (16.0/70 - 24)	13	DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L	395	1175	544	3556	IND	-	TL	158 A8
	400/80 - 24 (15.5/80 - 24)	DW 13	DW 12 ; DW 13 L ; DW 14 L	405	1250	570	3781	IND	20	TL	162 A8
	440/80 - 24 (17.0/80 - 24)	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	455	1315	610	3986	IND	22	TL	168 A8
	460/70 - 24 (17.5 L - 24)	DW 15 L	DW 14 L ; DW 16 L	460	1250	562	3784	IND	-	TL	159 A8
	500/70 - 24 (19.5 L - 24)	DW 16 L	DW 15 L ; DW 18 L	505	1300	579	3926	IND	-	TL	164 A8
∅ 26"	480/80 - 26 (18.4 - 26)	DW 15 L	DW 16 L	490	1410	643	4272	IND	-	TL	160 A8
∅ 28"	440/80 - 28 (16.9 - 28)	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	450	1420	632	4299	IND	-	TL	156 A8

IND: Industrial

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.

BKT GROWING TOGETHER