IS standard

GROWING TOGETHER

DESERT KING

PRODUCT DATA SHEET

Bias

E-7

DESERT KING

DESERT KING is best suited for loose soil, sandy terrain and paver applications with desert trucks. The optimized rib tread design offers excellent flotation and directional stability. Its strong nylon casing and heavy-duty bead are specially developed for low pressure operations. DESERT KING provides also high punctures resistance and a longer tire life.

Technologies

Heavy Duty

Strong Casing

Performance

Excellent flotation

Stability

High Puncture Resistance

Durability

	Tire size	Type	TRA CODE	PR	LI/SS	Version	TKPH	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM	
													Rec.	Alt.
∅ 25"	18.00 - 25 DT	TL	E-7	16	-	STD	-	470	1535	635	4405	16	10.00/1.5	-
	21.00 - 25 DT	TL	E-7	16	-	STD	-	570	1660	708	4906	18	15.00/3.0	-
	29.5 - 25 DT	TL	E-7	28	-	STD	-	770	1822	786	5392	21	25.00/3.5	-

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.