IS standard

GROWING TOGETHER

EARTHMAX
RADIAL OTR TIRES

SR 25 PLUS

PRODUCT DATA SHEET

Radial

G-2/L-2

A8

175

Technologies

All Steel

Performance

Traction

Self-Cleaning

Durability

EARTHMAX SR 25 PLUS

RADIAL OTR TIRES

EARTHMAX SR 25 PLUS (G-2/L-2) is an All Steel radial tire, which has been specially designed for motor graders and loaders operating in the most severe road construction or mining applications. Its non-directional tread design offers excellent self-cleaning properties in addition to traction and stability off the road.

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM	
													Rec.	Alt.
∅ 24"	14.00 R 24	TL	G-2/L-2	*	153 A8/ 175 A2	CRC	-	359	1372	626	4146	25	8.00 TG	9.00 GR

CRC: Cut Resistance Compound

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.

EN / 08-2024

BKT GROWING TOGETHER