IS standard

GROWING TOGETHER

# EARTHMAX
RADIAL OTR TIRES

# SR 30

PRODUCT DATA SHEET

Radial

E-3/L-3

B

208

Technologies

All Steel

Performance

Traction

Cut Resistance

Stability

Durability

# EARTHMAX SR 30

RADIAL OTR TIRES

EARTHMAX SR 30 (E-3/L-3) is an *All Steel* radial tire which is dual-purposed for loaders and articulated dump trucks. The multi-layer steel belts and the rigid block pattern provide excellent traction, stability and durability. The special cut-resistant compound makes EARTHMAX SR 30 the ideal solution for a variety of harsh operating conditions.

| | Tire size | Type | TRA CODE | STAR RATING | LI/SS | Version | TKPH | O.W. (mm) | O.D. (mm) | SLR (mm) | RC (mm) | TREAD DEPTH (mm) | RIM Rec. | RIM Alt. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| ∅ 25" | 15.5 R 25 | TL | E-3/L-3 | **/* | 160 B/ 169 A2 | CRC | 130 | 397 | 1276 | 574 | 3809 | 27 | 12.00/1.3 | - |
| | 17.5 R 25 | TL | E-3/L-3 | **/* | 167 B/ 176 A2 | CRC | 150 | 446 | 1347 | 606 | 4021 | 29 | 14.00/1.5 | - |
| | 17.5 R 25 | TL | L-3 | *** | 188 A2 | CRC | - | 446 | 1347 | 606 | 4021 | 29 | 14.00/1.5 | - |
| | 20.5 R 25 | TL | E-3/L-3 | **/* | 177 B/ 186 A2 | CRC | 170 | 529 | 1487 | 663 | 4439 | 32 | 17.00/2.0 | 17.00/1.7 |
| | 20.5 R 25 NEWSIZE | TL | L-3 | ** | 193 A2 | CRC | - | 529 | 1487 | 663 | 4439 | 32 | 17.00/2.0 | 17.00/1.7 |
| | 23.5 R 25 | TL | E-3/L-3 | **/* | 185 B/ 195 A2 | CRC | 200 | 612 | 1607 | 711 | 4797 | 34 | 19.50/2.5 | - |
| | 26.5 R 25 | TL | E-3 | ** | 193 B | CRC | 230 | 689 | 1742 | 766 | 5200 | 38 | 22.00/3.0 | - |
| | 26.5 R 25 | TL | E-3/L-3 | **/* | 193 B/ 202 A2 | CRC | 230 | 689 | 1742 | 766 | 5200 | 38 | 22.00/3.0 | - |
| | 26.5 R 25 | TL | L-3 | * | 202 A2 | CRC | - | 689 | 1742 | 766 | 5200 | 38 | 22.00/3.0 | - |
| | 29.5 R 25 | TL | E-3 | ** | 200 B | CRC | 270 | 765 | 1861 | 818 | 5555 | 42 | 25.00/3.5 | - |
| | 29.5 R 25 | TL | E-3/L-3 | **/* | 200 B/ 208 A2 | CRC | 270 | 765 | 1861 | 818 | 5555 | 42 | 25.00/3.5 | - |
| | 29.5 R 25 | TL | L-3 | * | 208 A2 | CRC | - | 765 | 1861 | 818 | 5555 | 42 | 25.00/3.5 | - |

CRC: Cut Resistant Compound

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.