IS standard

GROWING TOGETHER

EARTHMAX
RADIAL OTR TIRES

SR 33

PRODUCT DATA SHEET

Radial

K

168

Technologies

All Steel

Performance

Traction

Durability

EARTHMAX SR 33

RADIAL OTR TIRES

EARTHMAX SR 33 is a radial tire for multipurpose trucks. Its multi-block tread pattern has been specially designed to guarantee extraordinary traction on soft, sandy, or muddy surfaces. EARTHMAX SR 33 provides outstanding stability in addition to best self-cleaning properties. The strong All Steel casing features excellent durability and resistance to snag and punctures.

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM Rec.	RIM Alt.
∅ 20"	14.00 R 20	TL	-	-	164/ 160 J	STD	-	390	1250	576	3840	23	10.0	9.0 ; 10.00 W
	335/80 R 20	TL	-	-	150 K	STD	-	335	1047	464	3145	16	11.0	-
	365/80 R 20 (14.5 R 20)	TL	-	-	152 K	STD	-	360	1096	496	3318	16	11.0	-
	395/85 R 20	TL	-	-	168 J	STD	-	394	1184	538	3589	25	10.00 W	10.00 HF

STD: Standard

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.