IS standard

BKT
GROWING TOGETHER

EARTHMAX
RADIAL OTR TIRES
SR 412

PRODUCT DATA SHEET

NEWSIZE

EARTHMAX SR 412

RADIAL OTR TIRES

Radial

L-4

B

215

Technologies

Steel Belted

All Steel

Performance

High Puncture Resistance

Steering Control

Traction

EARTHMAX SR 412 (E-4/L-4) is an All Steel radial tire specially designed for Articulated Dump Trucks, Loaders and Dozers. The unique E-4 deep tread pattern ensures excellent traction. Thanks to its strong All Steel casing and belts, EARTHMAX SR 412 can carry heavy loads providing excellent stability as well as best resistance to snags and punctures. EARTHMAX SR 412 features a squared shoulder design that maximizes ground contact for excellent maneuverability.

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM Rec.	RIM Alt.
∅ 25"	29.5 R 25	TL	E-4	**	200 B	CRC	252	765	1865	834	5543	54	25.00/3.5	-
	750/65 R 25 (30/65 R 25)	TL	E-4	**	190 B	CRC	229	780	1602	715	4838	55	24.00/3.0	22.00/3.0 ; 25.00/3.0
	750/65 R 25 (30/65 R 25)	TL	E-4/L-4	**/*	190 B/ 202 A2	CRC	229	780	1602	715	4838	55	24.00/3.0	22.00/3.0 ; 25.00/3.0
∅ 29"	800/65 R 29	TL	E-4/L-4	**/*	198 B/ 208 A2	CRC	206	790	1805	825	5490	58	27.00/3.0	24.00/3.5 ; 25.00/3.5
	800/65 R 29 NEWSIZE	TL	L-4	**	215 A2	CRC	-	790	1805	825	5490	58	27.00/3.0	24.00/3.5 ; 25.00/3.5

CRC: Cut Resistant Compound

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.

EN / 07-2025