IS standard

GROWING TOGETHER

EARTHMAX
RADIAL OTR TIRES

SR LOADER

PRODUCT DATA SHEET

Radial

L-3

B

208

Performance

Cut and Chip Resistance

Durability

High Load Capacity

High Puncture Resistance

Self-Cleaning

Traction

EARTHMAX SR LOADER

RADIAL OTR TIRES

EARTHMAX SR LOADER is an OTR tire designed for loading and dozing operations as well as for Articulated dump truck application. Its All Steel casing along with multi-layer steel belts and a unique tread compound provide exceptional resistance to snags and punctures resulting in an extended service life. EARTHMAX SR LOADER features a unique tread pattern providing top self-cleaning properties and excellent traction on several types of terrain.

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM Rec.	RIM Alt.
∅ 25"	20.5 R 25	TL	E-3/L-3	**/*	177 B/ 186 A2	CRC	170	530	1475	649	4384	29	17.00/2.0	-
	23.5 R 25	TL	E-3/L-3	**/*	185 B/ 195 A2	CRC	200	612	1605	706	4770	31	19.50/2.5	-
	26.5 R 25	TL	E-3/L-3	**/*	193 B/ 202 A2	CRC	230	681	1735	763	5179	33	22.00/3.0	-
	29.5 R 25	TL	E-3/L-3	**/*	200 B/ 208 A2	CRC	270	768	1859	818	5549	37	25.00/3.5	-

CRC: Cut Resistant Compound

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.