IS standard

GR 288

PRODUCT DATA SHEET

Bias

GR 288

GR 288 (G-2/L-2) is a versatile bias-ply tire for graders or loaders. It is ideal for use in construction, site preparation, road building, and other soft or muddy environments. The self-cleaning tread pattern provides excellent traction, and you can expect a long tire life as a result of the special cut-and-chip-resistant compound.

Performance

Cut and Chip Resistance

Self-Cleaning

Stability

Traction

	Tire size	Type	PR	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM Rec.	RIM Alt.
∅ 25"	15.5 - 25	TL	12	-	STD	385	1270	572	3772	12.00/1.3	12.00/ 1.3 (DC)
	17.5 - 25	TL	12	-	STD	445	1330	596	3950	14.00/1.5	14.00/ 1.5 (DC) ; 14.00/ 1.3 (DC)
	17.5 - 25	TL	16	-	STD	445	1330	596	3950	14.00/1.5	14.00/ 1.3 (DC)
	17.5 - 25	TT	20	-	DB HD	445	1330	596	3950	14.00/1.5	14.00/ 1.3 (DC)
	20.5 - 25	TL	16	-	STD	520	1480	656	4396	17.00/2.0	17.00/1.7
	20.5 - 25	TL	20	-	STD	520	1480	656	4396	17.00/2.0	17.00/1.7
	23.5 - 25	TL	16	-	STD	595	1610	708	4782	19.50/2.5	-
	23.5 - 25	TL	20	-	STD	595	1610	708	4782	19.50/2.5	-

STD: Standard - DB HD: Dual Bead Heavy Duty

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.

EN / 08-2024