IS standard

GROWING TOGETHER

LIFTMAX LM 63

PRODUCT DATA SHEET

NEWSIZE

EN / 09-2025

Radial

A8

176

Technologies

All Steel

Performance

Stability

Comfort

LIFTMAX LM 63

LIFTMAX LM 63 has been specially developed for industrial and logistics operations. The *All-Steel* radial tire features a strong casing reinforced by multilayer steel belts that reduce vibration while providing enhanced stability and comfort. LIFTMAX LM 63 features a 3-rib tread design that ensures low rolling resistance as well as good wet grip and uniform tread wear, delivering improved handling performance. In addition, the deep tread extends the tire's service life.

	Tire size	Type	STAR RATING	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM Rec.	RIM Alt.
∅ 8"	180/70 R 8 (18 X 7 R 8)	TL	-	125 A5	STD	170	460	-	-	4.33 R	-
	180/70 R 8 IMP (18 X 7 R 8)	TL	-	120 A8	STD	170	460	-	-	4.33 R	-
∅ 9"	6.00 R 9	TL	-	121 A5	STD	160	542	-	-	4.00 E	-
∅ 10"	6.50 R 10	TL	-	128 A5	STD	176	592	-	-	5.00 F	5.50 F
∅ 12"	7.00 R 12	TL	-	136 A5	STD	195	675	-	-	5.00 S	-
∅ 15"	7.00 R 15	TL	-	143 A5	STD	198	738	-	-	5.50	5.00
	8.25 R 15	TL	-	153 A5	STD	240	844	-	-	6.5	7.0
∅ 20"	12.00 R 20 NEWSIZE	TL	-	176 A5	STD	325	1140	-	-	8.5	8.0

STD: Standard

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.