IS standard

GROWING TOGETHER

LIFTMAX LM 81

PRODUCT DATA SHEET

Radial

A8

200

LIFTMAX LM 81

LIFTMAX LM 81 has been specifically designed and engineered for heavy forklift. Its aggressive and robust tread pattern together with the unique Antistatic tread compound ensures excellent wear properties and a long service life. The strong All Steel casing and the reinforced sidewall provide maximum stability and handling during lift mode, together with superior traction. In addition, its radial casing absorbs surfaces irregularities to provide better riding comfort and increase operator's confidence. LIFTMAX LM 81 is Antistatic compliant, and all its sizes are capable of dissipating static charge from the vehicle.

Technologies

Special Antistatic Compound

All Steel

Performance

Stability

Durability

Handling and Comfort

Traction

	Tire size	Type	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM Rec.	RIM Alt.
∅ 8"	5.00 R 8	TL	111 A5	STD	138	471	-	-	3.00 D	3.25 I ; 3.75 I
	150/75 R 8	TL	113 A5	STD	150	430	-	-	4.33 R	-
	150/75 R 8 IMP	TL	109 A8	STD	150	430	-	-	4.33 R	-
	180/70 R 8	TL	125 A5	STD	170	453	-	-	4.33 R	-
	180/70 R 8 IMP (18 x 7 R 8)	TL	120 A8	STD	170	453	-	-	4.33 R	-
∅ 9"	6.00 R 9	TL	121 A5	STD	160	540	-	-	4.00 E	-
	200/75 R 9	TL	134 A5	STD	202	530	-	-	6.00 E	-
∅ 10"	6.50 R 10	TL	128 A5	STD	178	590	-	-	5.00 F	5.50 F
	225/75 R 10	TL	142 A5	STD	220	595	-	-	6.50 F	-
∅ 12"	7.00 R 12	TL	136 A5	STD	195	675	-	-	5.00 S	-
	250/75 R 12	TL	152 A5	STD	260	680	-	-	8.00	-
∅ 15"	7.00 R 15	TL	143 A5	STD	199	745	-	-	5.50	5.00
	7.50 R 15	TL	146 A5	STD	212	778	-	-	6.00	6.50
	8.25 R 15	TL	153 A5	STD	234	836	-	-	6.50	7.00

STD: Standard

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

Radial

A8

200

Technologies

Special Antistatic Compound

All Steel

Performance

Stability

Durability

Handling and Comfort

Traction

	Tire size	Type	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM Rec.	RIM Alt.
∅ 15"	225/75 R 15 (28 X 9 R 15)	TL	149 A5	STD	226	712	-	-	7.00	-
	250/70 R 15	TL	153 A5	STD	230	735	-	-	7.00	7.50
	315/70 R 15	TL	165 A5	STD	305	834	-	-	8.00	-
	355/65 R 15	TL	170 A5	STD	350	840	-	-	10.15	-
∅ 20"	9.00 R 20	TL	160 A5	STD	255	1028	-	-	7.00	7.50
	10.00 R 20	TL	166 A5	STD	275	1066	-	-	7.50	8.00
	11.00 R 20	TL	170 A5	STD	288	1092	-	-	8.00	8.50
	12.00 R 20	TL	176 A5	STD	314	1134	-	-	8.50	8.00
	12.00 R 20	TL	176 A5	IND	314	1134	-	-	8.50	8.00
∅ 24"	12.00 R 24	TT	178 A5	STD	310	1235	-	-	8.50	9.00
	12.00 R 24	TL	178 A5	STD	310	1235	-	-	8.50	9.00
	14.00 R 24	TL	193 A5	STD	388	1415	-	-	10.00 W	10.00 ; 10.00 WA
	14.00 R 24	TL	193 A5	IND	388	1415	-	-	10.00 W	10.00 ; 10.00 WA
∅ 25"	16.00 R 25	TL	200 A5	STD	440	1530	-	-	11.25/2.00	13.00/2.00

STD: Standard - IND: Industrial

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.

EN / 09-2025