IS standard

GROWING TOGETHER

LOADER PLUS

PRODUCT DATA SHEET

Bias

L-3

Performance

Cut Resistance

Traction

LOADER PLUS

LOADER PLUS (L-3) is a bias-ply tire specially designed for loaders. The tread compound provides cut-and-chip-resistant properties and suites best for loading and dozing operations.

	Tire size	Type	TRA CODE	PR	LI/SS	Version	TKPH	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM Rec.	RIM Alt.
∅ 25"	14.00 - 25	TT	L-3	20	-	STD	-	375	1368	630	4050	26	10.00/1.5	-
	17.5 - 25	TT	L-3	16	-	STD	-	440	1345	622	3980	26	14.00/1.5	-
	17.5 - 25	TL	L-3	16	-	STD	-	440	1345	622	3980	26	14.00/1.5	-
	17.5 - 25	TT	L-3	20	-	DB	-	440	1345	622	3980	26	14.00/1.5	-
	20.5 - 25	TT	L-3	16	-	STD	-	540	1490	685	4410	29	17.00/2.0	-
	20.5 - 25	TL	L-3	16	-	STD	-	540	1490	685	4410	29	17.00/2.0	-
	20.5 - 25	TT	L-3	20	-	STD	-	540	1490	685	4410	29	17.00/2.0	-
	20.5 - 25	TL	L-3	20	-	STD	-	540	1490	685	4410	29	17.00/2.0	-
	23.5 - 25	TT	L-3	16	-	STD	-	610	1640	749	4855	32	19.50/2.5	-
	23.5 - 25	TL	L-3	16	-	STD	-	610	1640	749	4855	32	19.50/2.5	-
	23.5 - 25	TL	L-3	24	-	STD	-	610	1640	749	4855	32	19.50/2.5	-
	23.5 - 25	TT	L-3	20	-	STD	-	610	1640	749	4855	32	19.50/2.5	-
	23.5 - 25	TL	L-3	20	-	STD	-	610	1640	749	4855	32	19.50/2.5	-
	26.5 - 25	TL	L-3	32	-	STD	-	680	1740	796	5150	36	22.00/3.0	-
	26.5 - 25	TL	L-3	28	-	STD	-	680	1740	796	5150	36	22.00/3.0	-
	29.5 - 25	TL	L-3	32	-	STD	-	760	1860	849	5544	39	25.00/3.5	-
	29.5 - 25	TL	L-3	28	-	STD	-	760	1860	849	5544	39	25.00/3.5	-

STD: Standard - DB: Dual Bead

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.

EN / 08-2024

BKT GROWING TOGETHER