IS standard

BKT
GROWING TOGETHER

PL 801

PRODUCT DATA SHEET

Bias

A8

114

Performance

Cut and Chip Resistance

Durability

Stability

PL 801

PL 801 has been specially designed for hay harvesting applications with rotor rakes/tedders and for logistics operations with forklifts. It features excellent stability as well as high cut and chip resistance. PL 801 ensures an extended tire life-cycle.

	Tire size	RIM Rec.	RIM Alt.	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
Ø 5"	23 X 5 (23 X 5 [- 13])	3.75 P	-	154	640	-	-	STD	6	TT	-
Ø 8"	5.00 - 8	3.00 D	3.25 I	135	468	-	-	STD	8	TT	-
	5.00 - 8	3.00 D	3.25 I	135	468	-	-	STD	10	TT	-
	18 X 7 - 8 (180/70 - 8)	4.33 R	5.00 F	173	470	-	-	STD	14	TT	-
	18 X 7 - 8 (180/70 - 8)	4.33 R	5.00 F	173	470	-	-	STD	16	TT	-
Ø 9"	6.00 - 9	4.00 E	-	157	543	-	-	SPL	10	TT	-
	6.00 - 9	4.00 E	-	157	543	-	-	STD	10	TT	114 A8
	6.00 - 9	4.00 E	-	157	543	-	-	STD	12	TT	-
	21 X 8 - 9 (200/75 - 9)	6.00 E	7.00 E	200	535	-	-	STD	14	TT	-
	21 X 8 - 9 (200/75 - 9)	6.00 E	7.00 E	200	535	-	-	STD	16	TT	-
Ø 10"	6.50 - 10	5.00 F	5.50 F	185	595	-	-	STD	10	TT	-
Ø 12"	7.00 - 12	5.00 S	-	189	692	-	-	STD	12	TT	-
	7.00 - 12	5.00 S	-	189	692	-	-	STD	14	TT	-

STD: Standard - SPL: Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

Bias

A8

114

Performance

Cut and Chip Resistance

Durability

Stability

	Tire size	RIM Rec.	RIM Alt.	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
∅ 15"	5.50 - 15	4.50 E DT	4.50 E SDC	157	670	-	-	STD	8	TT	-
	7.00 - 15 (29 X 8 - 15)	5.5	4.33 R ; 5.0	200	750	-	-	STD	12	TT	-
	7.00 - 15 (30 X 8 - 15)	6.0	5.50 BD ; 5.5	206	775	-	-	STD	12	TT	-
	7.00 - 15 (30 X 8 - 15)	6.0	5.50 BD ; 5.5	206	775	-	-	STD	14	TT	-
	7.50 - 15	6.0	6.00 S ; 6.5	220	785	-	-	STD	12	TT	-
	7.50 - 15 (7.50 - 15 [32" OD])	6.0	6.00 S ; 6.5	220	814	-	-	STD	14	TT	-
	7.50 - 15	6.0	6.00 S ; 6.5	220	785	-	-	STD	14	TT	-
	8.15 - 15 (28 X 9 - 15)	7.0	7.00 BD	215	720	-	-	STD	12	TT	-
	8.15 - 15 (28 X 9 - 15)	7.0	7.00 BD	215	720	-	-	STD	14	TT	-
	8.25 - 15	6.5	6.0 ; 7.0	236	854	-	-	STD	12	TT	-
	8.25 - 15	6.5	6.0 ; 7.0	236	854	-	-	STD	14	TT	-
	250 - 15 (250/70 - 15)	7.50 BD	7.0 ; 7.5	235	745	-	-	STD	16	TT	-
	250 - 15 (250/70 - 15)	7.50 BD	7.0 ; 7.5	235	745	-	-	STD	20	TT	-
	300 - 15 (315/70 - 15)	8.00 BD	8.0	295	840	-	-	STD	18	TT	-

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.

EN / 08-2024