IS standard

GROWING TOGETHER

POWER TRAX HD

PRODUCT DATA SHEET

Bias

A8

173

Technologies

Deep Tread

POWER TRAX HD

POWER TRAX HD premium tire is specially designed for equipment in port and underground mining applications. Its deep tread, the extra thick sidewall and the tough casing provide exceptional durability minimizing the risk of punctures and accidental damages. The tire features excellent cut and chip resistance, which is particularly suitable for rough and hard surfaces. The specially designed rim guard ensures protection against flats and wheel damage in the rim flange area.

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
∅ 20"	12.00 - 20	TT	20	172 A8	IMP	320	1150	-	-	8.50	9.0
	12.00 - 20	TT	20	-	STD	320	1150	-	-	8.50	9.0
	12.00 - 20	TT	28	173 A8	IMP	320	1150	-	-	8.50	9.0
	12.00 - 20	TT	28	-	STD	320	1150	-	-	8.50	9.0

STD: Standard - IMP: Implement

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.

EN / 08-2024